TABLE OF CONTENTS

Introduction	
What is DOE-2?	4
About This Manual	4
Other Documentation	5
What Does a DOE-2 Run Look Like?	7
Sample Input	7
Sample Output	12
Structure of DOE-2	18
Uses for DOE-2	20
How Has DOE-2 Been Validated?	20
Weather Files	21
Program-Related Software and Services	21
Building Description Language (BDL)	
BDL Instructions	1. 1
Terminator	1. 1
Comments	1. 1
INPUT Command	1. 1
END Command	1. 1
COMPUTE Command	1. 2
Keywords	1. 2
U-Names and Referenced Commands	1. 2
Choosing U-Names	1. 3
LIKE Keyword	
Subcommands	1. 4
Building Description	1. 4
Internal Zania	
Internal Zoning	1. 4
Use of Comments	1. 5
Alternative Runs	1. 5
Schedules	1.6
Flexibility of Input Format	1.6
What Does a DOE-2 Run Look Like?	1. 9
Sample Input	1. 9
Sample Output	1.13
LOADS	
Introduction	2. 1
LOADS Input Instructions	2. 2
Limitation on Number of Commands	2. 2
Description of LOADS Input Instructions	2. 2
SYSTEMS	
Introduction	3. 1
General Discussion of Systems	3. 1
Variable Air Temperature Systems (Constant Volume) (SZRH, PSZ)	3. 2
Reheat Systems (Constant Volume) (RHFS)	3. 3
Air Mixing Systems (Constant Volume) (DDS, MZS, PMZS)	3. 4
Variable Air Volume Systems (Constant Temperature) (VAVS, PVAVS)	3. 5
Hybrid Systems	2 6

Other System Types in DOE-2	3. 6			
Specific HVAC Distribution Systems				
Single Zone Fan System (SZRH)				
Constant-Volume Reheat Fan System (RHFS)				
Multizone Fan System (MZS)	3.13			
Dual-Duct Fan System (DDS)	3.19			
Variable-Volume Fan System (VAVS)	3.23			
Powered Induction Unit (PIU)				
Two-Pipe Fan Coil System (TPFC)	3.26 3.32			
Four-Pipe Fan Coil System (FPFC)				
Residential System (RESYS)	3.35 3.38			
with DX Cooling and Heating Coil				
with Heat Pump	3.38			
Packaged Single Zone Air Conditioner System with Options (PSZ)	3.42			
Packaged Multizone Fan System (PMZS)	3.45			
Packaged Variable-Air-Volume System (PVAVS)	3.48			
Packaged Terminal Air Conditioner (PTAC)	3.51			
with DX Cooling and Electric Resistance Heating	3.51			
with Air-to-Air Heat Pump	3.52			
Packaged Total Gas Solid Desiccant System (PTGSD)	3.55			
Unit Heater (UHT)	3.59			
Unit Ventilator (UVT)	3.61			
Description of SYSTEMS Input Instructions	3.63			
Limitation on the Number of Commands	3.63			
Reset Schedule Instructions	3.64			
PLANT				
Introduction	4. 1			
Suggested Sequence of PLANT Program Input.	4. 1			
Description of ELEC-STM-BOILER				
Description of STM-BOILER	4. 2 4. 2			
Description of HW-BOILER				
D A DI DO INII DOMEN				
Description of ABSOR1-CHLR	4. 3 4. 3			
Description of ABSOR2-CHLR	4. 4			
Description of ABSORG-CHLR.	4. 4			
Description of HERM-CENT-CHLR.	4. 4			
Description of HERM-REC-CHLR	4. 5			
Description of DBUN-CHLR	4. 5			
Description of ENG-CHLR	4. 5			
Description of COOLING-TWR	4. 6			
Description of DHW-HEATER and ELEC-HEATER				
Description of PLANT Input Instructions.	4. 6			
Limitation on the Number of Commands	4. 7			
Chillers	4. 7			
Chillers	4.11			
Towers	4.12			
Boilers	4.13			
Domestic Hot-Water Heaters	4.13			
Pumps	4.13			

ECONOMICS		
Introduction		5. 1
Example ECON	OMICS Input	5. 1
Description of E	CONOMICS Input Instructions	5. 2
Examples of BL	OCK-CHARGES	5. 9
Yearly Rate		5. 9
		5. 9
Time of Use R	ate	5.11
	ectricity Tariffs	5.16
		5.16
	Tariff	5.16
	Tariff	5.17
	ges	5.18
Time of Use a	nd Seasonal Demand Charges	5.18
APPENDIX A	Additional Capabilities of DOE-2	
APPENDIX B	Example of Input and Output	
APPENDIX C	Basic Reports	
APPENDIX D	DOE-2 Materials Library	
	List of Basic Commands and Keywords list of commands and keywords found in this manual	,
APPENDIX F	Basic BDL Summary	

The Building Description Language (BDL) Summary lists defaults, limits, and abbreviations for all commands and keywords found in this manual

What Is DOE-2?

DOE-2 is an up-to-date, unbiased, well-documented public-domain computer program for building energy analysis. DOE-2 predicts the hourly energy use and energy cost of a building given hourly weather information and a description of the building and its HVAC equipment and utility rate structure. DOE-2 is a portable FORTRAN program that can be used on a large variety of computers, including PC's. Using DOE-2, designers can determine the choice of building parameters that improve energy efficiency while maintaining thermal comfort. The purpose of DOE-2 is to aid in the analysis of energy usage in buildings; it is not intended to be the sole source of information relied upon for the design of buildings. The judgment and experience of the architect/engineer still remain the most important elements of building design.

About This Manual

During the 15 years that DOE-2 has been in existence, it has grown to three times its original size due to the addition of new capabilities. As a result, using the program can be difficult not only for the novice but also for the experienced user.

The enormous number of input and output variables from which you can choose is only part of the problem. Up until now there has been no attempt to give you guidance as to what is considered "basic" and what might be termed "finesse". Learning to use DOE-2 is analogous to learning a card game: first you learn how to bid, then to follow suit, then to trump. It is only after the "basic" rules have been mastered that the idea of a "finesse" can enter the game. This manual is aimed at introducing you to the basic rules of DOE-2.

DOE-2 Basics covers approximately 80% of normal simulation applications, yet requires you to be familiar with only 25% of the input variables available in the program. These variables have been chosen from our long experience of assisting the most experienced users prepare their inputs.

There is a real danger in preparing a manual with a limited set of variables because so many useful features of the program are left out. To compensate for this, we have provided, in Appendix A, a directory of the more complex features of DOE-2.

Other Documentation

In addition to this DOE-2 Basics, there are six other pieces of documentation:

- Reference Manual (2.1A)
 - detailed instructions on how to use all features of Version 2.1A of the program
- Supplement (2.1E)
 - a companion volume to the Reference Manual (2.1A), it contains detailed discussions and instructions for using the enhancements introduced into subsequent versions of the program
- BDL Summary (2.1E)
 - summarizes all input commands and keywords
 - lists defaults, limits, abbreviations
- Sample Run Book (2.1E)
 - shows input and output for simple and complex buildings and systems
 - illustrates most program features
 - a complete set of sample inputs and outputs is available on the mainframe DOE-2 tape for you to examine, run, and/or edit; a reduced set of samples is distributed on diskette with the PC versions of DOE-2.
- Engineers Manual (2.1A)
 - describes engineering and mathematical basis of program calculations
 - lists sources of algorithms
- User News
 - published quarterly
 - distributed free of charge
 - features articles on the effective use of DOE-2
 - lists program problems and bug fixes
 - provides a directory of DOE-2 related software products

Any program user may receive the *User News* free of charge. To be put on the distribution list, please write the Simulation Research Group, Bldg. 90 - Room 3147, Lawrence Berkeley Laboratory, Berkeley, CA 94720.

DOE-2 manuals are available from the National Technical Information Service, 5285 Port Royal Road, Springfield, VA 22161; tel. (703) 487-4650, Fax (703) 321-8547. Contact NTIS for price and delivery information.


Title of Document (version of DOE-2)	NTIS Order Number
Reference Manual (2.1A)	LBL-8706, Rev.2
Supplement (2.1E)	*
DOE-2 Basics (2.1E)	- new york and
BDL Summary (2.1E)	- 14 to 14 t
Sample Run Book (2.1E)	13.8 ±1.0 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Engineers Manual (2.1A)	DE-830-04575

At the time this manual went to press, NTIS reference numbers had not yet been assigned. Please call Kathy Ellington at (510) 486-5711, or fax to (510) 486-4089, for reference numbers.

What does a DOE-2 run look like?

Following are the input (complete with a system, plant, and energy rate) and selected output reports for the single zone building shown below. (A more detailed version of this building, with five zones and a plenum, is shown in Appendix B.)

BM034






Figure 1.1: Simple Structure — Single Zone Building. LEFT-1, FRONT-1, etc. are user-defined names.

Sample Input

INPUT LOADS .. TITLE LINE-1 *SIMPLE EXAMPLE FOR DOE-2 BASICS* .. JAN 1 1974 THRU DEC 31 1974 ... RUN-PERIOD ABORT ERRORS .. DIAGNOSTIC WARNINGS .. LOADS-REPORT SUMMARY - (LS-C) .. \$ CHICAGO LOCATION BUILDING-LOCATION LATITUDE = 42.0 LONGITUDE = 88.0 ALTITUDE - 610 TIME-ZONE - 6 AZIMUTH - 0 .. \$ CONSTRUCTIONS AND GLASS TYPES -LAYERS MATERIAL - (WD01, PW03, IN02, GP01) ... WA-1-2 RB-1-1 -LAYERS MATERIAL - (RG01, BR01, IN22, WD01) INSIDE-FILM-RES = .76 .. LAYERS - RB-1-1 .. ROOF-1 -CONSTRUCTION WALL-1 LAYERS - WA-1-2 .. -CONSTRUCTION FLOOR-1 U-VALUE = .05 .. -CONSTRUCTION -CONSTRUCTION U-VALUE = .5 .. WINDOW-1 -GLASS-TYPE SHADING-COEF = .9 PANES = 2 .. SHADING-COEF - .8 PANES - 1 .. G-DOOR -GLASS-TYPE \$ OCCUPANCY SCHEDULE OCCUPY-1 -SCHEDULE THRU DEC 31 (MON, FRI) (1,8) (0) (9, 11) (1) (12,14) (.8,.4,.8) (15, 18) (1) (19,21) (.5,.1,.1) (22, 24)(0)(1,24) (0) .. (WEH) \$ LIGHTING SCHEDULE LIGHTS-1 -SCHEDULE THRU DEC 31 (MON, FRI) (1,8) (0.05)

(15,18) (1) (19,21) (.6,.2,.2) (22,24) (0.05)

(1,24) (.05) ..

(WEH)

(9,14) (.9,.95,1,.95,.8,.9)

\$ OFFICE EQUIPMENT SCHEDULE EQUIP-1 -SCHEDULE THRU DEC 31 (MON, FRI) (1,8) (.02) (9,14) (.8) (15,20) (.8,.7,.5,.5,.3,.3) (21,24) (.02) (WEH) (1,24) (.02) ... \$ INFILTRATION SCHEDULE INFIL-1 -SCHEDULE THRU MAR 31 (ALL) (1,24) (1) THRU OCT 31 (ALL) (1,24) (0) THRU DEC 31 (ALL) (1,24) (1) .. \$ SPACE DEFINITION OFFICE-ENV PEOPLE-SCHEDULE - OCCUPY-1 -SPACE-CONDITIONS LIGHTING-SCHEDULE - LIGHTS-1 EQUIP-SCHEDULE - EQUIP-1 LIGHTING-TYPE - REC-FLUOR-RV LIGHTING-W/SQFT - 1.5 EQUIPMENT-W/SQFT - 1 AREA/PERSON - 110 PEOPLE-HEAT-GAIN - 450 - 70 FLOOR-WEIGHT INF-METHOD - AIR-CHANGE INF-SCHEDULE - INFIL-1 AIR-CHANGES/HR = .6 .. OFFICE -SPACE SPACE-CONDITIONS - OFFICE-ENV AREA - 5000 VOLUME - 40000 ... \$ WALLS, WINDOWS, AND DOORS FRONT-1 -EXTERIOR-WALL HEIGHT - 8 WIDTH - 100 AZIMUTH-180 CONSTRUCTION - WALL-1 ... WF-1 -WINDOW WIDTH - 45 HEIGHT - 4 GLASS-TYPE - WINDOW-1 .. DF-1 -WINDOW WIDTH - 8 HEIGHT - 7 GLASS-TYPE = G-DOOR .. \$ GLASS DOOR RIGHT-1 -EXTERIOR-WALL HEIGHT - 8 WIDTH - 50 CONSTRUCTION - WALL-1 ... AZIMUTH - 90 WR-1 -WINDOW LIKE WF-1 WIDTH - 25 ..

WIDTH - 100

CONSTRUCTION - WALL-1 ..

HEIGHT - 8 .

AZIMUTH - 0

BACK-1

-EXTERIOR-WALL

WB-1 -WINDOW LIKE WF-1 WIDTE - 45 .. DB-1 WIDTH - 8 HEIGHT - 7 -DOOR CONSTRUCTION - D1 .. \$ WOOD DOOR LEFT-1 HEIGHT - 8 WIDTH - 50 -EXTERIOR-WALL AZIMUTH - 270 CONSTRUCTION - WALL-1 ... -WINDOW LIKE WF-1 WL-1 WIDTH -25 .. TOP-1 -ROOF HEIGHT - 50 WIDTH - 100 CONSTRUCTION - ROOF-1 ...

AZIMUTH - 180

BOTTOM-1 -UNDERGROUND-FLOOR AREA - 5000

-SCHEDULE

CONSTRUCTION - FLOOR-1 ..

END ..

FANS-ON

COMPUTE LOADS ..

INPUT SYSTEMS ..

(MON, FRI) (1,7) (0) (8,18) (1) (19,24) (0) (WEH) (1,24)(0) .. COOLSETPT -SCHEDULE THRU DEC 31 (MON, FRI) (1,7) (99) (8,18) (76) (19,24) (99) (WEH) (1,24)(99) .. HEATSETPT -SCHEDULE THRU DEC 31 (MON, FRI) (1,7) (55) (8,18) (72) (19,24) (55) (WEH) (1,24)(55) .. DHW -SCHEDULE THRU DEC 31 (MON, FRI) (1,7) (0) (8,18) (1) (19,24) (0) (WEH) (1,24)(0) .. OFFICE -ZONE - 72 DESIGN-HEAT-T DESIGN-COOL-T - 74 HEAT-TEMP-SCH - HEATSETPT COOL-TEMP-SCH - COOLSETPT - 20 .. OA-CFM/PER -SYSTEM AC-SYST SYSTEM-TYPE - SZRH

MAX-SUPPLY-T

MIN-SUPPLY-T

FAN-SCHEDULE

DRYBULB-LIMIT

OA-CONTROL ZONE-NAMES

THRU DEC 31

- 110

- FANS-ON

- (OFFICE) ..

- 55 NIGHT-CYCLE-CTRL - CYCLE-ON-FIRST

> - 68 - TEMP